

# H&H HAL Hi-Deck Trailers



Model shown has top rails, aluminum wheels, and aluminum floor

## Standard Features

- 5" aluminum channel top frame.
- 6" aluminum channel tongue.
- 3" aluminum channel crossmembers on 28" on center spacing.
- Powder coated steel substructures.
- 2<sup>5</sup>/<sub>16</sub>" adjustable height coupler with dual safety chains.
- 5000lb Set-back jack.
- 2x8 wood floor with 2" dovetail.
- Drop-down docklegs.
- Multiple stake pocket tie-downs.
- Aluminum 6' 3" ramps with carrier.
- Tandem 3500lb spring axles – 7000lb GVWR
- 4-wheel electric brakes with break-away kit & battery.
- ST205-15 C rated bias tires on white wheels.
- Full LED lighting system.

MODEL	DESCRIPTION	DECK WIDTH	OVERALL DECK LENGTH
HAL 16' +DOVE 18'	102"x16'+ 2' Dovetail HAL Aluminum Hi-Deck	100"	18ft
HAL 18' +DOVE 20'	102"x18'+ 2' Dovetail HAL Aluminum Hi-Deck	100"	20ft
HAL 20' +DOVE 22'	102"x20'+ 2' Dovetail HAL Aluminum Hi-Deck	100"	22ft
HAL 22' +DOVE 24'	102"x22'+ 2' Dovetail HAL Aluminum Hi-Deck	100"	24ft



## Upgrade Options

## Description

9990lb GVWR	Includes tandem 5200lb brake axles, 5" channel aluminum frame, 14" on center cross member spacing, ST225/75R15 radials on 6-bolt white wheels, break-away kit with battery.
12000lb GVWR	Includes tandem 6000lb brake axles, 6" channel aluminum frame, 14" on center cross member spacing, ST235/75R15 radials on 8-bolt white wheels, break-away kit with battery.
14000lb GVWR	Includes tandem 7000lb brake axles, 6" channel aluminum frame upgrade, 4" channel crossmembers, 14" on center cross member spacing, drop-down dock legs, ST235/75R15 radials on 8-bolt white wheels, break-away kit with battery.
Upgrade to 205/75R15 Radial Tires	
Aluminum Wheels	Upgrade to radial tires on aluminum wheels.
Extruded Aluminum Flooring	Planked style.
Rope Rails	Aluminum rope rails.
Additional Stake Pockets	placed on the front of the trailer.
D-rings	Swivel style.

Additional options may be available.

