

H&H RSA Rail Side Single Axle Utility Trailers

STANDARD FEATURES

- 14" tall side aluminum rails.
- Angle 6061-T6 aluminum extrusion lower frame.
- Rectangular aluminum tube uprights and top rail.
- 4" channel aluminum tongue with brace.
- 2" A-frame coupler with dual safety chains.
- 2000lb coupler mounted jack.
- Treated 2x8 wood decking.
- Aluminum radius fenders.
- 3500lb idler axle with EZ lube hubs-- 2990lb GVWR.
- ST205/75R15 radial tires on white wheels.
- 54" long, aluminum ramp gate with fold-forward storage and spring loaded J-hooks with no pin removal - 1500lb rating.
- Full LED lighting.
- Wiring enclosed in conduit.



MODEL	DESCRIPTION	DECK WIDTH	DECK LENGTH
RSA 5x8F RS	5x8' Rail Side Aluminum Flatbed RSA	60"	8ft
RSA 5x10F RS	5x10' Rail Side Aluminum Flatbed RSA	60"	10ft
RSA 5x12F RS	5x12' Rail Side Aluminum Flatbed RSA	60"	12ft
RSA 5x14F RS	5x14' Rail Side Aluminum Flatbed RSA	60"	14ft
RSA 5.5x10F RS	5.5x10' Rail Side Aluminum Flatbed RSA	66"	10ft
RSA 5.5x12F RS	5.5x12' Rail Side Aluminum Flatbed RSA	66"	12ft
RSA 5.5x14F RS	5.5x14' Rail Side Aluminum Flatbed RSA	66"	14ft
RSA 8x10F RS	8x10' Rail Side Aluminum Flatbed RSA	76"	10ft
RSA 8x12F RS	8x12' Rail Side Aluminum Flatbed RSA	76"	12ft
RSA 8x14F RS	8x14' Rail Side Aluminum Flatbed RSA	76"	14ft
RSA 8.5x10F RS	8.5x10' Rail Side Aluminum Flatbed RSA	82"	10ft
RSA 8.5x12F RS	8.5x12' Rail Side Aluminum Flatbed RSA	82"	12ft
RSA 8.5x14F RS	8.5x14' Rail Side Aluminum Flatbed RSA	82"	14ft



Upgrade Options

- Extruded Aluminum Plank Deck
- Bi-fold Ramp Gate Upgrade
- 60" Wide Side Ramp Gate - 12ft minimum
- ATV Ramps - 12ft minimum
- 3500lb Brake Axle Upgrade
- Aluminum Wheels
- Spare Wheel and Tire
- Wheel Chock



H&H TRAILERS LLC STRONGLY RECOMMENDS HITCHING YOUR TRAILER TO YOUR TOW VEHICLE BEFORE LOADING!
PHOTOS MAY SHOW OPTIONAL EQUIPMENT. MODELS AND OPTIONS ARE SUBJECT TO CHANGE.