

H&H SSA Solid Side Tandem Axle Utility Trailers



H&H Trailers® does not recommend using utility trailers as car haulers.

STANDARD FEATURES

- 15" tall formed 1/8" polished aluminum diamond plate main body.
- 5" channel aluminum tongue.
- 2⁵/₁₆" A-frame Posi-Lock coupler.
- 5000lb recessed jack in set-back position.
- .060 teardrop aluminum fenders.
- Tandem 3500lb spring axles with EZ lube hubs – 7000lb GVWR.
- 4-wheel electric brakes with break-away kit & battery.
- ST205/75R15 radial tires on white wheels.
- Treated 2x8 wood decking.
- 54" Long, aluminum lay down ramp gate with fold flat storage feature. 1500lb load rating.
- LED tail and marker lights with wiring enclosed in conduit.

MODEL	DESCRIPTION	DECK WIDTH	DECK LENGTH
SSA8 UT 12 SS	8x12' Aluminum SSA Solid 15" Panel Sides tandem trailer	76"	12ft
SSA8 UT 14 SS	8x14' Aluminum SSA Solid 15" Panel Sides tandem trailer	76"	14ft
SSA8 UT 16 SS	8x16' Aluminum SSA Solid 15" Panel Sides tandem trailer	76"	16ft
SSA8 UT 18 SS	8x18' Aluminum SSA Solid 15" Panel Sides tandem trailer	76"	18ft
SSA8 .5UT 12 SS	8.5x12' Aluminum SSA Solid 15" Panel Sides tandem trailer	82"	12ft
SSA8 .5UT 14 SS	8.5x14' Aluminum SSA Solid 15" Panel Sides tandem trailer	82"	14ft
SSA8 .5UT 16 SS	8.5x16' Aluminum SSA Solid 15" Panel Sides tandem trailer	82"	16ft
SSA8 .5UT 18 SS	8.5x18' Aluminum SSA Solid 15" Panel Sides tandem trailer	82"	18ft
SSA8 .5UT 20 SS	8.5x20' Aluminum SSA Solid 15" Panel Sides tandem trailer	82"	20ft



Spring Loaded J hooks Standard
Unlatch ramp with no clip removal!

- Upgrade Options**
- Extruded Aluminum Plank Deck
 - Bi-fold Ramp Gate Upgrade
 - 60" Wide Side Ramp Gate – 16' minimum
 - Box Top Rope Rail
 - Aluminum Stake Pockets
 - Torsion Axles
 - Aluminum Wheels
 - Spare Wheel and Tire
 - Wheel Chock
 - Toolbox



Extruded Aluminum Plank Deck Option

H&H TRAILERS LLC STRONGLY RECOMMENDS HITCHING YOUR TRAILER TO YOUR TOW VEHICLE BEFORE LOADING!
PHOTOS MAY SHOW OPTIONAL EQUIPMENT. MODELS AND OPTIONS ARE SUBJECT TO CHANGE.