

H&H SSA Solid Side Single Axle Utility Trailers

STANDARD FEATURES

- 15" tall formed 1/2" polished aluminum diamond plate main body.
- 4" channel aluminum tongue.
- 2" A-frame Posi-Lock coupler.
- 2000lb swivel-up jack.
- .060 aluminum radius fenders.
- 3500lb axle with leaf spring suspension & EZ lube hubs – 2990lb GVWR.
- ST205/75R15 radial tires on white wheels.
- Treated 2x8 wood decking.
- 54" long, aluminum lay down gate with fold forward storage feature and spring loaded J-hooks. 1500lb load rating.
- LED tail and marker lights with wiring enclosed in conduit.

Low Maintenance!

33% Less Weight than Steel!



MODEL	DESCRIPTION	DECK WIDTH	DECK LENGTH
SSA 5 X8F SS	5x8' Aluminum Flatbed SSA Solid Panel Sides single axle	60"	8ft
SSA 5 X10F SS	5x10' Aluminum Flatbed SSA Solid Panel Sides single axle	60"	10ft
SSA 5 X12F SS	5x12' Aluminum Flatbed SSA Solid Panel Sides single axle	60"	12ft
SSA 5 X14F SS	5x14' Aluminum Flatbed SSA Solid Panel Sides single axle	60"	14ft
SSA 5.5 X10F SS	5.5x10' Aluminum Flatbed SSA Solid Panel Sides single axle	66"	10ft
SSA 5.5 X12F SS	5.5x12' Aluminum Flatbed SSA Solid Panel Sides single axle	66"	12ft
SSA 5.5 X14F SS	5.5x14' Aluminum Flatbed SSA Solid Panel Sides single axle	66"	14ft
SSA 8 X10F SS	8x10' Aluminum Flatbed SSA Solid Panel Sides single axle	76"	10ft
SSA 8 X12F SS	8x12' Aluminum Flatbed SSA Solid Panel Sides single axle	76"	12ft
SSA 8 X14F SS	8x14' Aluminum Flatbed SSA Solid Panel Sides single axle	76"	14ft
SSA 8.5 X10F SS	8.5x10' Aluminum Flatbed SSA Solid Panel Sides single axle	82"	10ft
SSA 8.5 X12F SS	8.5x12' Aluminum Flatbed SSA Solid Panel Sides single axle	82"	12ft
SSA 8.5 X14F SS	8.5x14' Aluminum Flatbed SSA Solid Panel Sides single axle	82"	14ft



*Spring Loaded J hooks
Unlatch ramp with no clip removal!*

H&H TRAILERS LLC STRONGLY RECOMMENDS HITCHING YOUR TRAILER TO YOUR TOW VEHICLE BEFORE LOADING!
PHOTOS MAY SHOW OPTIONAL EQUIPMENT. MODELS AND OPTIONS ARE SUBJECT TO CHANGE.

Upgrade Options

- Extruded Aluminum Plank Deck
- Bi-fold Ramp Gate Upgrade
- 60" Wide Side Ramp Gate – 12ft minimum
- Box Top Rope Rail
- Aluminum Stake Pockets
- Electric Brake Axle with Break-away Safety Kit and Battery
- Aluminum Wheels
- Spare Wheel and Tire
- Wheel Chock